

# BeneHeart C1A

## Automated External Defibrillator (AED)

### Defibrillator

Operations	Semi-automatic and fully automatic versions
Waveform	Biphasic Truncated exponential (BTe), with automated voltage and duration compensation for patient impedance
Range of selected energy	100 to 360 J (adult) 10 to 100 J (child)
Energy default	200-300-360 J (adult) 50-70-100 J (child)

indication of operating time (at 20±5 °C, typical).

Weight 300 g

#### Electrode Pads

Type Pre-connected, disposable for adult/child

Shelf life 5 years (from date of manufacture)

#### CPR Sensor<sup>2</sup>

Weight Approximately 180 g (without battery)

Thickness 17.5 to 19 mm

#### Automatic Self-test

Auto-test Daily, weekly, monthly, quarterly

Status indicator Visual indicators indicating system readiness

#### Data Storage

Events Up to 500 events

Voice recording Up to 1 hour

CPR data Up to 5 hours

Self-test reports 1000 records

Data export Through AED-Alert™ 2.0 system

#### Communications

Wireless data transfer to AED-Alert™ 2.0 system Through 5G/2.4G Wi-Fi or cellular (4G)<sup>3</sup>

network

Alert™ 2.0 system

<sup>1</sup> Requiring to configure with CPR sensor

<sup>2</sup> For further information about the availability of CPR sensor, please contact with your local sales representatives.

<sup>3</sup> For further information about the availability of 4G data transfer and AED-Alert™ 2.0 system, please contact with your local sales representatives.

[www.mindray.com](http://www.mindray.com)

P/N:ENG-C2 Datasheet -210285X2P-20190830

©2019 Shenzhen Mindray Bio-Medical Electronics Co., Ltd. All rights reserved.

**mindray**  
healthcare within reach

